


JB1550S



PRODUCT SPECIFICATIONS

Working height-full lift (A)	3970 (mm)	Articulation height-full lift (B)	3021 (mm)
Bucket bottom height-full lift (C)	2813 (mm)	Height of overhead guard (D)	2008 (mm)
Total length-with bucket (E)	3521 (mm)	Overall length-without bucket (F)	2763 (mm)
Flip down angle-full lift (G)	39 (°)	Discharge height-full lift (H)	2270 (mm)
Discharge distance-full lift (J)	658 (mm)	Inclination angle - full lift (K)	96 (°)
Upward inclination angle (L)	27 (°)	Wheel base (M)	1093 (mm)
Wheel base (N)	1412 (mm)	Ground clearance (P)	190 (mm)
Departure angle (Q)	22 (°)	Bucket width (R)	1730 (mm)
Overall width-without bucket (S)	1676 (mm)	Tail length (W)	991 (mm)
Turning radius-with bucket (X)	2156 (mm)	Turning radius-without bucket (Y)	1353 (mm)
Turning radius-tail (Z)	1648 (mm)		



ENGINE

Brand	YANMAR
Power	35.5kW Certified EPA Tier4F & Euro Stage 5 compliant.
Number of cylinders	4
Fuel	Diesel fuel

HYDRAULIC ELECTRICAL SYSTEM

Standard hydraulic flow rate of attachments	80 (L/min)
Maximum oil supply pressure for accessories	21 (Mpa)
Fuel tank capacity	80 (L)
Hydraulic oil tank capacity	80 (L)
Operating voltage	DC12 (V)

Operation method	Pilot hydraulic control
------------------	-------------------------

BASIC TECHNICAL PARAMETERS

Rated load	800 (kg)
Tipping load	1600 (kg)
Operating weight	2987 (kg)
Maximum driving speed	12.6 (km/h)
Tire specifications	10-16.5
Standard bucket	66"
Bucket width	1730 (mm)
Flat pack capacity	0.4 (m ³)

RJB Heavy Industries Ltd.

Mailing Address: #133 8 - 6014 Vedder Rd, Chilliwack, BC V2R5P5
Canada Office: + 1 604 807 0195 WhatsApp/Cellular: + 1 604 789 0195
E: info@rjbhi.com W: rjbhi.com

